


COLZE MASCLE / FEMELLA



TAP MASCLE CEC

DN	α	S	Z1	Z2	L1	L2
160	15°	3.6	14	28	82	72
160	30°	3.6	25	40	82	72
160	45°	3.6	67	50	82	72
160	67°30'	3.6	60	74	82	74
160	87°30'	3.6	84	100	83	74
200	15°	4.9	18	35	100	86
200	30°	4.9	30	49	100	86
200	45°	4.5	46	64	100	84
200	67°30'	4.5	73	88	100	86
200	87°30'	4.5	105	122	100	85
250	15°	6.1	19	40	134	103
250	30°	6.1	37	59	134	103
250	45°	6.1	58	80	135	101
250	87°30'	6.1	132	154	136	103
315	15°	7.7	23	52	144	120
315	30°	7.7	47	74	144	118
315	45°	7.7	73	100	144	118
315	87°30'	7.7	166	192	144	114
400	15°	9.8	83	80	175	175
400	30°	9.8	132	142	175	175
400	45°	9.8	91	126	165	140
400	87°30'	9.8	211	244	160	140
500	15°	12.2	150	160	160	250
500	30°	12.2	165	230	160	250
500	45°	9.8	103	152	160	150

DN	D1	S	L1
160	180	3.6	49
200	223	5.6	59
250	282	6.1	90
315	350	7.7	93
400	440	9.8	95
500*	558	11.8	120

NOTA: *Manipulat

NORMA UNE-EN 1401-1

NORMA UNE-EN 1401-1