


DERIVACIÓ SIMPLE 45°  
MASCLE / FEMELLA



DERIVACIÓ SIMPLE 45°  
FEMELLA / FEMELLA

DN	DN1	S	S1	Z1	Z2	Z3	L1	L2	L3
160	110	3.6	3.0	2	168	176	82	74	56
160	125	3.6	3.0	12	180	185	83	74	62
160	160	3.6	---	38	205	205	83	71	71
200	110	4.9	3.0	17	191	200	100	86	56
200	125	4.5	3.0	7	201	212	100	86	62
200	160	4.5	3.6	18	228	232	100	86	74
200	200	4.9	4.5	45	251	251	100	85	85
250	160	6.1	3.6	3	250	261	131	103	74
250	200	6.1	4.5	24	275	280	134	103	86
250	250	6.1	---	57	311	311	134	101	101
315	160	7.7	3.6	33	289	306	144	114	75
315	200	7.7	4.5	5	317	337	144	114	85
315	250	7.7	6.1	28	335	344	156	114	99
315	315	7.7	---	73	392	392	144	114	114
400	160*	10.2	3.4	69	319	385	165	170	95
400	200*	10.2	4.7	50	355	435	165	180	105
400	250*	10.2	6.6	35	440	445	165	180	130
400	315*	10.2	8.2	73	480	530	160	170	135
400	400*	10.2	10.2	170	535	535	165	175	170
500	160*	12.2	3.8	-65	450	680	200	250	90
500	200*	12.2	4.7	87	400	575	200	250	110
500	250*	12.2	6.4	-10	510	530	200	250	110
500	315*	12.2	8.2	-45	475	503	200	250	135
500	400*	12.2	10.2	115	615	640	200	250	180
500	500*	12.2	12.2	240	665	675	200	250	255

DN	DN1	S	S1	Z1	Z2	Z3	L1	L2
160	125	47	30	41	180	185	74	62
160	160	36	36	52	203	203	72	72
200	125	59	36	54	228	232	86	74
200	160	59	36	54	228	232	86	74

NORMA UNE-EN 1401-1

NORMA UNE-EN 1401-1